

Forecasting and Updating Traffic Flow.

Thomas Bengtsson

Department of Statistics
University of California - Berkeley

NCAR
June 16, 2005.

This work is supported by the National Science Foundation

Outline

1. Sequential DA using ensemble Kalman filter.
2. ensemble Kalman filter \rightarrow “full” Bayes DA.
3. Traffic example: DA in non-linear & non-Gaussian system.
4. DA in high-dimensional systems: what is reasonable?

Some to live by...

1. “Better to have the approximate solution to the correct problem than the exact solution to the wrong problem” -*J. Tukey*

Some to live by...

1. “Better to have the approximate solution to the correct problem, than the exact solution to the wrong problem” -*J. Tukey*.
2. “Flying is like milk, everybody needs it’ -*D.Nychka*.

Some to live by...

1. “Better to have the approximate solution to the correct problem than the exact solution to the wrong problem” -*J. Tukey*
2. “Flying is like milk, everybody needs it’ -*D. Nychka*.
3. “It is easier to solve a problem if you know a lot about it” -*G. W. Bush*.

Where are we?

1. Sequential DA using ensemble Kalman filter.
2. ensemble Kalman filter \rightarrow “full” Bayes DA.
3. Traffic example: DA in non-linear & non-Gaussian system.
4. DA in high-dimensional systems: what is reasonable?

Data Assimilation & Atmospheric State Prediction

Approximation to reality:

$$\text{Weather observations} \longrightarrow \mathbf{y}_t = H(\mathbf{x}_t) + \boldsymbol{\epsilon}_t$$

$$\text{Atmospheric State} \longrightarrow \mathbf{x}_t = G(\mathbf{x}_{t-1}) + \boldsymbol{\eta}_t$$

\mathbf{y}_t , data

\mathbf{x}_t , unobserved

H maps state to observation (linear or non-linear)

G highly nonlinear (chaotic, approximate, known)

$\boldsymbol{\eta}_t$ (parameterized) model error, stochastic forcing

$\boldsymbol{\epsilon}_t$ (gaussian) observation error, $\text{cov}(\boldsymbol{\epsilon}_t) = \mathbf{R}$

Goal: Real-time sequential assimilation and forecasting:

$$p(\mathbf{x}_t | \mathbf{Y}^{t-1}), \mathbf{y}_t \xrightarrow{\text{Bayes}} p(\mathbf{x}_t | \mathbf{Y}^t) \xrightarrow{G(\cdot)} p(\mathbf{x}_{t+1} | \mathbf{Y}^t), \mathbf{y}_{t+1} \xrightarrow{\text{Bayes}} p(\mathbf{x}_{t+1} | \mathbf{Y}^{t+1})$$

Ensemble Kf algorithm

- Let $\mathbf{x}_{t,i}^f \sim p(\mathbf{x}_t | \mathbf{Y}^{t-1})$ ($i = 1, \dots, M$) be a sample from the prior.
 - EnKF: With $\hat{\mathbf{P}}_t^f$ the sample covariance of $\{\mathbf{x}_{t,i}^f\}$, generate the posterior by

$$\mathbf{x}_{t,i}^a = \mathbf{x}_{t,i}^f + \hat{\mathbf{K}}_t \left(\mathbf{y}_t + \mathbf{e}_{t,i} - \mathbf{H}_t \mathbf{x}_{t,i}^f \right), \quad \mathbf{e}_{t,i} \sim (\mathbf{0}, \mathbf{R}).$$

- EnKf asymptotically optimal if $p(\mathbf{x}_t | \mathbf{Y}^{t-1})$ and $p(\mathbf{y}_t | \mathbf{x}_t)$ Gaussian;
- Common misconceptions about EnKf:
 1. Won't work if $p(\mathbf{x}_t | \mathbf{Y}^{t-1})$ is non-Gaussian or \mathbf{G} non-linear;
 - will provide BLUP as $M \rightarrow \infty$.
 - EnKf “respects” non-Gaussian properties in prior *sample*,
 2. Must have $M \sim \mathcal{O}(\dim(\mathbf{x}_t))$;
 - sample error depends on spectrum of \mathbf{P}_t^f ;
 - localization/tapering and square-root Kfs effectively remove errors due to sampling (*Furrer & Bengtsson, 2005*).

EnKF applied to Lorenz 96

- Atmospheric system with variables as k longitudes: z_1, \dots, z_{40} . (Subscript denotes spatial location.)
- Equations: for $j = 1, \dots, 40$,

$$\dot{z}_j = z_{j-1}(z_{j+1} - z_{j-2}) - z_j + F,$$

where F represents forcing.

- The equations contain quadratic nonlinearities mimicking advection:

$$\dot{u}_i \propto u_i \frac{\partial u_i}{\partial x} \approx u_i(u_{i'} - u_{i^*})/\delta x.$$

- F is chosen so that phase space is bounded and the system exhibits chaotic behavior.
- *Simulations*: $m = 10$, 'short' lead time ($\delta_t = .05$), 'observe' z_1, z_3, \dots, z_{39} : $y_j = z_j + \epsilon_j$, $\epsilon_j \sim N(0, 4)$,

Where are we?

1. Sequential DA using ensemble Kalman filter.
2. ensemble Kalman filter → “full” Bayes DA.
3. Traffic example: DA in non-linear & non-Gaussian system.
4. DA in high-dimensional systems: what is reasonable?

Particle Filter Approximation - I

- Consider the general state-space model

$$\begin{aligned}\text{Observation: } \mathbf{y}_{t+1} &\sim p(\mathbf{y}_{t+1}|\mathbf{x}_{t+1}) & (\mathbf{y}_t = H(\mathbf{x}_t) + \boldsymbol{\epsilon}_t) \\ \text{State evolution: } \mathbf{x}_{t+1} &\sim p(\mathbf{x}_{t+1}|\mathbf{x}_t) & (\mathbf{x}_t = G(\mathbf{x}_{t-1}) + \boldsymbol{\eta}_t)\end{aligned}$$

- (The numerator of) Bayes theorem in the sequential DA setting:

$$p(\mathbf{y}_{t+1}, \mathbf{x}_{t+1}) \propto p(\mathbf{y}_{t+1}|\mathbf{x}_{t+1}) \int p(\mathbf{x}_{t+1}|\mathbf{x}_t, \mathbf{Y}^t) p(\mathbf{x}_t|\mathbf{Y}^t) d\mathbf{x}_t.$$

- With $\mathbf{x}_{t,i}^a \sim p(\mathbf{x}_t|\mathbf{Y}^t)$, the numerator (and posterior) is approximated by

$$p(\mathbf{y}_{t+1}, \mathbf{x}_{t+1}) \propto p(\mathbf{y}_{t+1}|\mathbf{x}_{t+1}) \frac{1}{M} \sum_{j=1}^M p(\mathbf{x}_{t+1}|\mathbf{x}_{t,i}^a).$$

Particle Filter Approximation - II

(continued) $p(\mathbf{x}_{t+1}|\mathbf{Y}^{t+1}) \propto p(\mathbf{y}_{t+1}|\mathbf{x}_{t+1})\frac{1}{M} \sum_{j=1}^M p(\mathbf{x}_{t+1}|\mathbf{x}_{t,i}^a)$

- When the densities on RHS are Gaussian, this “yields” the EnKf.
- Implements Kf recursion as $M \rightarrow \infty$

- Generalization to non-Gaussian case:

Draw $\mathbf{x}_{t+1,i}^f \sim p(\mathbf{x}_{t+1}|\mathbf{x}_{t,i}^a)$, and let $w_i \propto p(\mathbf{y}_{t+1}|\mathbf{x}_{t+1,i}^f)$

- We could:

1. Accept $\mathbf{x}_{t+1,i}^f$, as a draw from **posterior**, with probability w_i ; or,
2. Approximate $p(\mathbf{x}_{t+1}|\mathbf{Y}^{t+1}) \approx \sum_{i=1}^M w_i \delta(\mathbf{x}_t - \mathbf{x}_{t+1,i}^f)$; or,
3. Develop further to produce: $w_{t,i} \rightarrow w_{t+1,i}$ (*particle filter*).

- Implements Bayes theorem as $M \rightarrow \infty$

- Particle filters/rejection/importance sampling algorithms are problematic in high-dimensions:
 - manifestation of the *curse-of-dimensionality*
- A particular *remedy* - The Auxiliary PF:

$$\begin{aligned} p(\mathbf{x}_{t+1}|\mathbf{y}_{t+1}) &\propto p(\mathbf{y}_{t+1}|\mathbf{x}_{t+1}) \int p(\mathbf{x}_{t+1}|\mathbf{x}_t)p(\mathbf{x}_t|\mathbf{Y}^t)d\mathbf{x}_t \\ &\approx p(\mathbf{y}_{t+1}|\mathbf{x}_{t+1}) \sum_j p(\mathbf{x}_{t+1}|\mathbf{x}_{t,j}^a) \\ &= \sum_j \frac{p(\mathbf{y}_{t+1}|\mathbf{x}_{t+1})}{p(\mathbf{y}_{t+1}|\mu_{t+1,j})} p(\mathbf{y}_{t+1}|\mu_{t+1,j}) p(\mathbf{x}_{t+1}|\mathbf{x}_{t,j}^a) \\ &= \sum_j \frac{p(\mathbf{y}_{t+1}|\mathbf{x}_{t+1})}{p(\mathbf{y}_{t+1}|\mu_{t+1,j})} g_{t,j} p(\mathbf{x}_{t+1}|\mathbf{x}_{t,j}^a) \end{aligned}$$

- Here, $p(\mathbf{y}_{t+1}|\mu_{t+1,j})$ is a “high-density” area of the likelihood.
- Will not “solve” problem of uneven weights.


Where are we?

1. Sequential DA using ensemble Kalman filter.
2. ensemble Kalman filter \rightarrow “full” Bayes DA.
3. Traffic example: DA in non-linear & non-Gaussian system.
4. DA in high-dimensional systems: what is reasonable?

State-Space Dynamics

- We use the simple model of Nagel and Schreckenberg (1992) as described in Helbing (2001):

A road stretch:



- Let there be L cells numbered left to right.
- Vehicles at locations x_1, \dots, x_N , with velocities v_1, \dots, v_N .
- Location of the lead vehicle is x_1 ; location of last vehicle is x_N .
- The state of the system is $\mathbf{x} = \{N, x_1, \dots, x_N, v_1, \dots, v_N\}$.
- The $v_i \in \{0, 1, \dots, 5\}$ and they satisfy $x_i + v_i \leq x_{i-1} - 1$.

State-Space Dynamics

The state transition mechanism $\mathbf{x} \rightarrow \mathbf{x}'$ is as follows:

1. **Change velocities:**

$$v_i \rightarrow v'_i = \max\{0, \min(v_i + 1, x_{i-1} - x_i - 1, 5) - \xi_i\},$$

where $\xi_i \stackrel{iid}{\sim} \text{Bernoulli}(p)$.

2. **Move vehicles:**

$$x_i \rightarrow x'_i = x_i + v'_i$$

3. **Adjust N :** Remove lead vehicle and/or add new vehicle: e.g.,


– If $x_1 + v'_1 > L$, the lead car is removed w.p. p_{exit} .

– a new car is added with probability p_{new} at location x_{N+1} chosen uniformly in $\{1, 2, \dots, \min(5, x'_N - v'_N - 1)\}$.

- The above defines $p(\mathbf{x}_{t+1} | \mathbf{x}_t, p)$.


Density Field

Illustration using $L = 200$, $N(\text{start}) = 50$, $p = .5$, $T = 500$.



Density and Average Velocity


Illustration using $L = 200$, $N(\text{start}) = 50$, $p = .5$, $T = 500$.



Observation Model

- A simple model for the observations: with $\epsilon_i \stackrel{iid}{\sim} N(0, \sigma^2)$,

$$Y^i = \begin{cases} 1 + \epsilon_i, & \text{cell } i \text{ occupied;} \\ \epsilon_i & \text{cell } i \text{ not occupied.} \end{cases}$$



- Assumption of independence (and normality) can be relaxed, but yields more complicated updating mechanism.
- The above defines $p(\mathbf{y}_{t+1} | \mathbf{x}_t, \sigma^2)$.

Particle Filter Approach

- A **sequential importance sampler** (e.g., particle filter) is obtained by a recursion on the weights $w_{t-1}^i \times p(\mathbf{y}_t | \mathbf{x}_t^i) \rightarrow w_t^i$:

$$\underbrace{\{\mathbf{z}_t^i, w_{t-1}^i\}}_{\text{prior}} \text{ and } \underbrace{p(\mathbf{y}_t | \mathbf{x}_{t,i})}_{\text{likelihood}} \xrightarrow{\text{Bayes}} \underbrace{\{\mathbf{x}_{t,i}, w_{t-1}^i \times p(\mathbf{y}_t | \mathbf{x}_{t,i})\}}_{\text{Posterior}}$$

- This produces a *likelihood filter*.
- We will adapt the PF to include observations from one-step ahead.

- The particle approach:

$$\begin{aligned} p(\mathbf{x}_{t+1}|\mathbf{Y}^{t+1}) &\propto p(\mathbf{y}_{t+1}|\mathbf{x}_{t+1}) \int p(\mathbf{x}_{t+1}|\mathbf{x}_t)p(\mathbf{x}_t|\mathbf{Y}^t)d\mathbf{x}_t \\ &\approx \frac{1}{M} \sum_{i=1}^M p(\mathbf{x}_{t+1}|\mathbf{x}_t^i)p(\mathbf{y}_{t+1}|\mathbf{x}_{t+1}) \end{aligned} \quad (1)$$

– Because of the system properties, we can sample from (1) directly, without using a rejection method or importance sampling.

Trick: Multiplying and dividing (1) by $p(\mathbf{y}_{t+1}|\mathbf{z}_t^i)$

$$\begin{aligned} p(\mathbf{x}_{t+1}|\mathbf{Y}^{t+1}) &\propto \frac{1}{M} \sum_{i=1}^M p(\mathbf{y}_{t+1}|\mathbf{x}_t^i) \frac{p(\mathbf{x}_{t+1}|\mathbf{x}_t^i)p(\mathbf{y}_{t+1}|\mathbf{x}_{t+1})}{p(\mathbf{y}_{t+1}|\mathbf{x}_t^i)} \\ &= \frac{1}{M} \sum_{j=1}^M p(\mathbf{y}_{t+1}|\mathbf{x}_t^j)p(\mathbf{x}_{t+1}|\mathbf{x}_t^j, \mathbf{y}_{t+1}) \end{aligned} \quad (2)$$

– Both densities in (2) are computable.


Sampling Procedure

Want: $p(\mathbf{x}_{t+1} | \mathbf{Y}^{t+1}) \approx \frac{1}{M} \sum_{j=1}^M p(\mathbf{y}_{t+1} | \mathbf{x}_t^j) p(\mathbf{x}_{t+1} | \mathbf{x}_t^j, \mathbf{y}_{t+1})$

- Assume a random sample $\mathbf{x}_t^i \sim p(\mathbf{x}_t | \mathbf{Y}^t)$ and generate a draw from posterior:
 1. Sample $\tilde{\mathbf{x}}_t^i = \mathbf{x}_t^i$ with probability proportional to $p(\mathbf{y}_{t+1} | \mathbf{x}_t^i)$
 2. Drawing $\mathbf{x}_{t+1}^i \sim p(\mathbf{x}_{t+1} | \tilde{\mathbf{x}}_t^i, \mathbf{y}_{t+1})$
- We do this M times to obtain updated particles $\{\mathbf{x}_{t+1}^i, \frac{1}{M}\}$.


Evaluating $p(\mathbf{y}_{t+1}|\mathbf{x}_t^j)$: Strategy

- In our setting, there are two aspects of the state-transition dynamics that drastically simplify simulation and particle filter approximations:
 1. vehicles are moved independently of one another; and, each vehicle can only move to one of two possible positions
 2. dependence of blocks of the y_i 's (measurement on cell i) on vehicle locations is very simple.
- Illustration: for particle j , let $b(i)$ be the set of possible locations for vehicle i at time $t + 1$



- Allows evaluation of $p(\mathbf{y}_{t+1}|\mathbf{x}_t^j) = \prod_i p(y_{t+1}^{b(i)}|\mathbf{x}_t^j)$

Evaluating $p(\mathbf{y}_{t+1}|\mathbf{x}_t^j)$: Specifically



- Let $b(i)$ index the data which depends on vehicle i . We want to evaluate

$$p(\mathbf{y}_{t+1}|\mathbf{x}_t^j) = \prod_{i=1}^N p(y_{t+1}^{b(i)}|\mathbf{x}_t^j).$$


– After much cancelation,

$$p(\mathbf{y}_{t+1}|\mathbf{x}_t^j) \propto \frac{p(y_{t+1}^{b(1)}|\mathbf{x}_t^j)}{\prod_{k \in b(1)} \phi\left(\frac{y_{t+1}^k}{\sigma}\right)} \prod_{i=2}^N \left[(1-p) \exp\left(\frac{y_{t+1}^{n(i)}}{\sigma^2}\right) + p \exp\left(\frac{y_{t+1}^{n(i)-1}}{\sigma^2}\right) \right].$$

- Draw state \mathbf{x}_t^j with probability $\frac{p(\mathbf{y}_{t+1}|\mathbf{x}_t^j)}{\sum_k p(\mathbf{y}_{t+1}|\mathbf{x}_t^k)}$.

Moving vehicles according to $\mathbf{x}_{t+1}^j \sim p(\mathbf{x}_{t+1} | \tilde{\mathbf{x}}_t^j, \mathbf{y}_{t+1})$

- Consider drawing $\mathbf{x}_{t+1}^j \sim p(\mathbf{x}_{t+1} | \tilde{\mathbf{x}}_t^j, \mathbf{y}_{t+1})$. This can again be done vehicle by vehicle:





– for vehicle i , we randomly choose the move corresponding to $n(i)$ or $n(i) - 1$, by evaluating the ratio

$$\alpha_i = \frac{p(\mathbf{y}_{t+1}^{b(i)} | \xi_i = 1) p(\xi_i = 1)}{p(\mathbf{y}_{t+1}^{b(i)} | \xi_i = 0) p(\xi_i = 0)} = \frac{p \exp\left(\frac{y_{t+1}^{n(i)-1}}{\sigma^2}\right)}{(1 - p) \exp\left(\frac{y_{t+1}^{n(i)}}{\sigma^2}\right)},$$

and ξ_i is then chosen to be 1 with probability $\alpha_i / (1 + \alpha_i)$.

Filter Performance

- Left: Density and estimated density.
- Right: Probability forecast verification:



What now?

- Remains to be done
 - Initialization.
 - Recursive parameter estimation.
- For realistic application:
 - Extend to correlated measurement errors.
 - How general is sampling scheme when model is more complex?